

CH-LCD56DUT 5.6" TFT LCD VIDEO Monitor

Features:

- ☐ Time & Money & Labor Saving
- ☐ Handy Compact Size and Shock resistance
- ☐ Carry On Rechargeable Battery
(12V.1.8AH For CH-LCD56DUT)
- ☐ With Charger
- ☐ 2CH A/V INPUT (CH-LCD56DUT)



Model	CH-LCD56DUT
LCD Panel	5.6" TFT LCD
Resolution	960x234
Brightness	350cd/m ²
Contrast Ratio	150:1
View Angle	R/L: ±45 U:+10 D:-30
System	NTSC/PAL Auto
Video input	1.0Vp-p at 75 composite(AV1.AV2)
Audio input	30mVp-p ~ 100mVp-p(AV1.AV2)
Audio output	0.5watt max (8Ω)
Video/Audio Connector	Min phone Tack w/ Min phone plug to RCA plug Adapter
User Control	Mode ◀▶power OSD controls
Batty	12V.1.8AH Chargeable
Charger	YES
Power supply	DC12V?10%Min tack
Power consumption	7.0 watt max
Operation Temperature	-10°C ~ +50°C
Storage Temperauure	-20°C ~ +65°C

Dimension (WxHxD)	243 x 171 x 73
Weight Net/Gross	2150g
Accessories	Carrying case phone plug to RCA plug wire Adapter