

PV755C

15" TFT LCD Color Display

Features:

- Analog and Digital signal input
- Active matrix LCD panel with 1024 x 768 XGA resolution
- 250 cd/m² high brightness and 16.7M displayable colors
- Auto-adjustment
- VESA wall mountable
- Multilingual user controls with OSD menu adjustment
- Full screen re-scaling capability
- 56~75 Hz refresh rate
- 31.5~60 kHz horizontal scan
- VESA DPMS power saving
- Kensington security lock function
- Integrated multimedia audio function



Specification:	
Model Name	PV755C
LCD Technology	-15" viewable diagonal screen -active matrix TFT colour LCD -1024 x 768 XGA resolution -350:1 contrast ratio (typ.) -250 cd/m ² brightness (typ.) -0.297mm x 0.297mm pixel pitch -Tr:8ms / Tf:22ms (typ.) response time -L/R= 60 ° /60 ° , U/D=40 ° /60 ° viewing angle, CR>=10
Resolution:	1024 pixels (H) x 768 lines (V)

Active Display Area:	304.1 (H)mm x 228.1 (V)mm
Displayable Colors:	16.7M colors
Synchronization Frequencies:	Horizontal Scan: 31.5 kHz to 60 kHz, Vertical Refresh: 56 Hz to 75 Hz, Pixel Frequency: 78.75MHz
Mounting Interface:	VESA Standard (75mm x 75mm)
Compatibility:	VESA XGA 1024 x 768, 60/70/75 Hz VESA SVGA 800 x 600, 56/60/72/75 Hz VESA VGA 640 x 480, 60/72/75 Hz, 640 x 400, 70Hz, 640 x 350, 70 Hz, 720 x 400, 70Hz Apple Macintosh 1024 x 768, 75 Hz; 832 x 624, 75 Hz; 640 x 480, 67Hz
Input Signal:	Analog Signal Input: Video:analog RGB 0.7 Vp-p Sync:separate sync Digital Signal Input: DVI-D
Auto-Adjustment:	Yes
Plug and Play:	VESA DDC 1/2 B
Multimedia Audio	Speaker 1w x 2 , built-in amplifier w/1w
I/O Connectors:	-DC power input -VGA 15-pin D-sub -DVI-D Connector -Audio-in -Earphone
User Controls:	-Multilingual on-screen menu adjustment -External brightness adjustment button -External auto-adjustment button -Screen image control items: ■Auto-Adjustment ■Contrast ■Horizontal Position ■Vertical Position ■Frequency ■Tracking ■Display Mode ■OSD Off-time ■Language ■Text-Graphic ■Reset ■Volume ■Mute ■Color Setting ■Color Adjustment (RGB)
Plug-and-Play	VESA DDC 1/2B
Power Savings:	VESA DPMS standard
Power Consumption:	30 watt (max.) < 5 watt (power save mode)

AC/DC Adapter:	External power adapter Input: Universal AC 100-240V (50-60Hz) Output: DC 12V UL, CSA, TUV, CE Mark compliant
Stand:	tilt (-5° ~30°)
Safety/Regulations:	FCC-B, CE-B, VCCI-II, BSMI, UL, CUL, TUV, TCO'99
Weight:	Unit: 4.4 kgs (9.7 lbs) Packed: 6.1 kgs (13.4 lbs)
Dimensions: (W x H x D)	Unit: 382.5 x 384.3 x 180.1mm Packed: 500 x 490 x 210 mm

Accessories :

- LCD Display with stand
- Power Adapter & Power Cord
- VGA Signal Cable
- DVI-D Cable
- Warranty Card
- Multilingual User's Manual
- DDC 1/2B diskette
- Audio-in Cable