

CH-LCD-174AV 17"TFT LCD VIDEO Monitor



Features:

- ☐ High Resolution: 1280x1024
- ☐ With Composite/S-Video Input
- ☐ With Audio Input
- ☐ On Screen Display

Specification

Model	CH-LCD-174AV
LCD Display:	17" active matrix TFT LCD panel
Pixel Pitch:	0.264(H) x 0.264(V) mm
Max. Resolution:	1280(H) x 1024(V) XGA
Set Size:	440(H) x 430(V) x 105(D) mm
Pack Size:	630(H) x 510(V) x 150(D) mm
Contrast Ratio:	400:1
Brightness:	250 cd/m ²
Response Time:	15/25ms
Display Color:	16.7 M
View Angle L+/R-	L/R:±65~85° U/D:±75°/85°
Pc Interface:	RGB analog 0.7V peak to peak
Video Sync.:	TTL positive or negative
Display Mode:	VGA, SVGA, XGA
Audio-in:	Phone jack RCA (x 1)
Video-in:	S & RCA (x1)
Signal Connector:	D-sub 15 pin
Front Control:	Power on/off with LED, OSD Menu, +/-Adjustment
OSD:	Contrast, Brightness, Auto Adjust, Clock, Phase, H-Position, V-Position
Input:	Pc / AV1 / S-Video (AV)
Power Adapter:	AC Input: 100-240V~1.8A, 50-60HzDC

Operating Conditions:

Output: 12V / 4.0A

Temperature: 0°C~50°C

Humidity: 20%~95%

Storage Conditions:

Temperature: -20°C~60°C

Humidity: 5%~95%

Certification:

FCC (DOC), CE-B, VCC-I, UL, TUV/GS

Weight:

Net Weight: 5.0Kgs,

Gross Weight: 6.5Kgs

