

Products

21 Inch Monitor



PANEL	21.2" ACTIVE MATRIX TFT LCD PANEL
EFFECTIVE DISPLAY AREA	430.1 (H) x 322.6 (V)mm
PIXEL PITCH	0.420(H) X 0.420(V)mm
RESPONSE TIME	R/F: 15/15
VIEWING ANGLE HORIZONTAL	75/75 DEGREE
VIEWING ANGLE VERTICAL	75/75 DEGREE
NUMBER OF PIXELS	1024(H) x 768 (V) pixel
NUMBER OF COLORS	16,777,216 Colors
CONTRAST	400:1
BRIGHTNESS	450 cd / _ (Typ.)
IMAGE	De-interlace support
CONTROL INTERFACE	Buttons and IR interface Full Function Easy to use IR/OSD 8 Language selection of OSD
INPUT I/O	On-board 15pin mini D-sub Optional JST connector for VGA-in
TV TUNNER	NTSC, Closed CaptionV-chip support (Optional) PAL/SECAM withTeletext support (Optional)
181 Pre-set Channels for	: VHF (Very High Freq. Ch2-13)
	: UHF (Ultra High Freq. Ch14-69)

	: STD, HRC, IRC (Cable)
	: HDTV 1080i (Optional)
VIDEO INPUT (NTSC/PAL/SECAM)	S-video, Composite, Components
VIDEO OUTPUT	Composite RCA Jack Video Out
SOUND	5W x 2 Speakers, Hi-Fi Earphone/RCA output
Audio Input :	3 channels RCA Phone Jack for Audio In
Audio Output :	Hi-Fi Earphone stereo, 1 Channel RCA MTS+SAP Stereo for NTSC / NICAM Stereo for PAL (Multichannel TV Sound, Second Audio Programming) Composite RCA Jack Audio Out
POWER CONSUMPTION	70W
INPUT VOLTAGE	12V / 7A
AC 100~240V, 50/60Hz	
STORAGE TEMPERATURE LIMITS	-20C to +60C
OPERATING TEMPERATURE LIMITS	0C to +50C
OPERATION HUMIDITY	LESS THAN 85%
ACCESSORIES	"User Manual, Adapter, Power Cord, Audio Cable, VGA Cable, Video Cable, Remote Control."
CERTIFICATE BSMI, MEET:	UL, C-UL, FCC, CE, CB, D-MARK
PRODUCT COLOR	SILVER BLACK / PURE BLACK
DIMENSION	
WEIGHT N.W.	KG.
WEIGHT G.W.	KG.